Application No.: 10/564.827

Docket No.: 59482,21820

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the

application:

(Currently Amended) Floor for a cargo compartment of an aircraft, 1.

comprising:

at least one floor element:

a functional unit for a cargo transportation means attached to said floor

element: and

3.

at least one floor beams supporting said at least one floor elements-and

adapted for connection to a skin of the aircraft, said floor element being rigidly

connected to said at least one floor beam and thereby forming a prefabricated

floor module adapted for installation in the aircraft, wherein

said floor beam is configured and adapted for connection to said skin of the

aircraft at a bottom portion of said aircraft, at a first side portion of said aircraft and at a

second side portion of said aircraft laterally opposite said first side portion.

(Previously Presented) Cargo-compartment floor according to Claim 2.

1, wherein said functional unit is mounted on said floor beam of the floor module.

(Previously Presented) Cargo-compartment floor according to Claim

1, wherein at least one of an electrical control device and a mechanical control

device for controlling said functional unit is connected to said functional unit.

Application No.: 10/564,827 Docket No.: 59482.21820

4. (Previously Presented) Cargo-compartment floor according to claim

1. wherein a transmission socket for power transmission is attached to said floor

module such that said transmission socket can be connected to a

complementarily shaped transmission connectors provided on an adjacent floor

module.

5. (Currently Amended) Cargo-compartment floor according to Claim 1.

wherein sections of at least one of cable channels, hydraulic conduits, water

conduits, and electrical leads are provided in the floor module and are adapted

such that they said sections can link to similar conducting devices in an

adjacent floor module to form an overall conducting system when the floor modules

are installed in the aircraft.

6. (Previously Presented) Cargo-compartment floor according to Claim

5. wherein the conducting device comprises branches that provide a connection

to predetermined locations on the floor element or the functional units.

(Previously Presented) Cargo-compartment floor according to Claim 7.

1. wherein assembly elements are provided on said floor modules to provide a

mechanically secure connection to adjacent floor modules during or after

installation of said floor modules in the aircraft.

Application No.: 10/564,827 PATENTS
Docket No.: 59482,21820 Customer No. 30734

8. (Previously Presented) Cargo-compartment floor according to Claim

1. wherein said floor element defines at least one inspection opening that is

closed by a floor-element section and that is provided to permit access to a bilge

space below said floor element.

9. (Previously Presented) Cargo-compartment floor according to Claim

8, wherein the floor-element section is fixed to said floor element by means of a

fast-action closure devices.

10. (Previously Presented) Cargo-compartment floor according to Claim

1. wherein said floor elements comprises a sealing device adapted to create a

tight seal between a space defined above and a space defined below said the

floor element.

11. (Previously Presented) Cargo-compartment floor according to Claim

1, wherein a leakproof connecting element is provided and is adapted for the

leakproof connection of said floor element to at least one of an adjacent floor

element said skin of the aircraft.

12. (Previously Presented) Cargo-compartment floor according to Claim

1, wherein a drainage device is provided to conduct fluids out of the cargo

compartment and to transfer said fluid into a corresponding drainage device of

an adjacent floor module.

Application No.: 10/564,827 PATENTS
Docket No.: 59482,21820 Customer No. 30734

(Previously Presented) Cargo-compartment floor according to Claim
 wherein said the floor module comprises at least one floor panel on which a

person can walk.

(Previously Presented) Cargo-compartment floor according to Claim
 wherein the floor module comprises at least one insulation device adapted to

insulate a lower portion of the fuselage of said aircraft.

15. (Previously Presented) Cargo-compartment floor according to Claim14, wherein said insulation device is disposed below said floor elements in the region of said supporting beam near said skin of said aircraft.

16. (Currently Amended) Cargo-compartment floor according to Glam Claim

1, wherein said floor module comprises at least one of a bulkhead and a fixation device for the attachment of a bulkhead thereto.

17. (Previously Presented) Cargo-compartment floor according to Claim
16, wherein said bulkheads are comprised at least in part of a ballistically-

resistant material.

18. (Previously Presented) Cargo-compartment floor according to Claim1, wherein said floor module comprises at least one of an EE racks, a mounting

Application No.: 10/564,827 Docket No.: 59482,21820

device for electronic components, a fixation device for electronic components

and a connecting devices for electronic components.

19. (Previously Presented) Cargo-compartment floor according to Claim

1, wherein said floor module comprises at least one of a water tank, a waste

water tank, a fixation device and a connecting devices for said tanks.

20. (Previously Presented) Cargo-compartment floor according to Claim

1, wherein said floor module comprises at least one of a lining element and a

mounting device for said elements, for lining the cargo compartment.

21. (Previously Presented) Cargo-compartment floor according to Claim

1. wherein said floor modules are constructed and are fastened to said skin of

the aircraft in such a way that after installation in the aircraft they can be

removed again in an arbitrary sequence.

22. (Withdrawn) Method for assembly of a floor for a cargo-compartment

of an aircraft, comprising the following steps:

providing a floor element;

providing a floor beam adapted for connection to a skin of the

aircraft:

Application No.: 10/564,827 Docket No.: 59482,21820

attaching said to said floor beam such that the floor elements together with the supporting elements form a prefabricated floor modules that can be handled as a unit:

lifting said a floor module into said cargo compartment;
fastening said the floor beam to said skin of the aircraft; and
repeating said above steps until the floor of the cargo compartment
has been completed.

- 23. (Withdrawn) Method according to Claim 22, comprising the additional step of mounting a functional unit for a cargo transportation means on the floor element before the latter is lifted into the cargo compartment.
- (Withdrawn) Method according to Claims 22 wherein a connecting step that follows the step of lifting into the cargo compartment in which at least one of control devices to control functional units;

conduction devices such as cable channels, hydraulic conduits, water conduits, electrical leads and similar conduction devices; and

drainage devices for conducting fluids out of the cargo compartment are connected to corresponding control devices, conducting devices and drainage devices associated with an adjacent floor module that has been fixed within the cargo compartment.

Application No.: 10/564,827 Docket No.: 59482,21820

25. (Withdrawn) Method according to Claim 24, wherein at least parts of the

connecting step is performed prior to the final fixation of the supporting elements to said

skin of the aircraft.

26. (Newly Added) A partially assembled aircraft, comprising:

a substantially cylindrical fuselage; and

a prefabricated cargo floor module comprising at least one floor element, a

functional unit for a cargo transportation means attached to said floor element and at

least one floor beam supporting said at least one floor element and adapted for

connection to a skin of said aircraft, said floor element being rigidly connected to said at

least one floor beam, wherein

said prefabricated cargo floor module rests within said substantially cylindrical

fuselage without said prefabricated cargo floor module being connected to said

fuselage.

27. (Newly Added) Floor for a cargo compartment of an aircraft, comprising:

at least one floor element;

a functional unit for a cargo transportation means attached to said floor element;

and

Application No.: 10/564.827 Docket No.: 59482.21820

at least one floor beam supporting said at least one floor element and adapted for connection to a skin of the aircraft, said floor element being rigidly connected to said at least one floor beam and thereby forming a prefabricated floor module adapted for installation in the aircraft, wherein

said floor module comprises at least one of a water tank and a waste water tank.

28. (Newly Added) An aircraft, comprising:

a substantially cylindrical fuselage; and

a prefabricated cargo floor module mounted at an ultimate position within said substantially cylindrical fuselage to form at least a portion of a cargo deck of said aircraft, wherein

said prefabricated cargo floor module comprises at least one floor element, a functional unit for a cargo transportation means attached to said floor element and at least one floor beam supporting said at least one floor element and adapted for connection to a skin of said aircraft, said floor element being rigidly connected to said at least one floor beam, and

said substantially cylindrical fuselage and said prefabricated cargo floor module are configured and adapted such that said substantially cylindrical fuselage receives and supports said prefabricated cargo floor module substantially at said ultimate position prior to said prefabricated cargo floor module being connected to said fuselage.

Application No.: 10/564,827 Docket No.: 59482.21820

29. (Newly Added) A prefabricated cargo floor module for mounting at an ultimate position within a substantially cylindrical fuselage of an aircraft to form at least a portion of a cargo deck of said aircraft, comprising:

at least one floor element;

a functional unit for a cargo transportation means attached to said floor element; and

at least one floor beam supporting said at least one floor element and adapted for connection to a skin of said aircraft, wherein

said floor element is rigidly connected to said at least one floor beam, and said prefabricated cargo floor module is configured and adapted to be received and supported by said substantially cylindrical fuselage substantially at said ultimate position prior to said prefabricated cargo floor module being connected to said fuselage.